

UX-8800

8x8 4k HDMI Matrix Switcher with HDCP 2.2


PureLink
digital solutions



The UX-8800 provides switching of up to four HDMI 2.0 inputs and outputs with advanced EDID management and HDCP 2.2 compliance. The UX-8800 offers full Ultra HD/4K support and multiple control options including RS-232C and LAN ports. PureLink's legendary EDID management system ensures compatibility across multiple display types and delivers consistent connectivity with quick, clean switching from source to display for a seamless presentation experience.

Key Features

- 8x8 HDMI 2.0 matrix switching
- Resolutions up to 4K@50/60 Hz (4:4:4 pixel format)
- HDMI 2.0, HDCP 2.2 support
- Advanced EDID Management
- Bi-directional RS232/LAN control
- Locking HDMI ports



Technical Specification	
Inputs	8 HDMI
Outputs	8 HDMI
Resolution	4096 x 2160 @50/60Hz RGB/YCbCr 4:4:4 8 bits, 4:2:0 10/12/16 bits
Data rate	18 Gbps
Operating temperature	32° ~ 117° F (0° to 47° C)
Storage temperature	- 40° ~ 158° F (-40° to 70° C)
Operating humidity	0 - 90% non-condensing
MTBF	95,000 hours
Supported format	HDMI 2.0
Compliance	HDCP 2.2
Accessories	DC +12V 5.0A Max 60w (power supply)
Dimensions (W x D x H)	19" x 8.0" x 1.75" in. 482.6 x 203.2 x 44.45 mm
Weight	6.7 lbs (3.04 kg)

