## PI155



D - Homi

## High Speed DisplayPort to HDMI Portsaver Adapter

Due to its high reliability, the PureInstall Series High Speed DisplayPort to HDMI Portsaver Adapter PI155 is particularly suited for professional applications and installations. The adapter facilitates the connection between an DisplayPort source and an HDMI cable.

- → High Speed Adapter for Video resolution to WUXGA (1920x1200)
- → Particularly qualified for professional applications and installations

Plug material:	PVC		
Contact material:	24-Carat gold plated		
Shielding:	Yes		
Connector 1:	DisplayPort Male (20pin)		
Dimension connector 1:	53,0 x 20,0 x 11,0 (mm)		
Connector 2:	HDMI Type A Female (19pin)		HIGH DEFINITION MULTIMEDIA INTERFACE
Dimension connector 2:	39,6 x 23,6 x 12,3 (mm)		
Cable			
Type:	Round cable		
Length:	0,10m		
Inner conductor material:	High purity tinned plated OFC Copper	A	В
AWG:	AWG28		C
Number of shieldings:	3-layer	В	
Shielding 1:	Aluminum foil (100% sealed)		
Shielding 2:	Aluminum foil (100% sealed)		
Shielding 3:	Braid (100% sealed)		A
Outer sheath material:	High flexible PVC	C	
Outer sheath diameter:	7,3mm		
Signal transmission			
Transmission modes:	Digital video signals		
Max. bandwith:	165 MHz		P
Max. Transfer rate:	3,72 Gbit/s		DisplayPort
Max. resolution:	1920x1200 WUXGA		
Supported color spaces :	8 bit RGB/YUV, Deep Color, x.v.Color™		x.v.Color
Supported audio standards:	-		A.v.Colol
Other supported standards:	HDCP, CEC, FullHD (1080i/p), HD ready (720i/p), SDTV (480i/p)		

Model No.	Color	Length
PI155	black	0,10 m